

DragonFly LDM[™]

Lights-out Digital Additive Manufacturing for Printed Electronics



Expanding Possibilities with Lights-out Digital Additive Manufacturing of Printed Electronics

Additively manufacturing functional circuits roundthe-clock with little or no operator intervention is now possible with the introduction of the DragonFly LDM™ (Lights-out Digital Manufacturing) precision additive manufacturing system from Nano Dimension. It's our most advanced platform for rapid prototyping and low-volume manufacturing of precision 3D printed electronics.

Benefits of the DragonFly LDM Technology

(24	
A	

24/7

Enables long, uninterrupted runs round the clock, with minimal supervision. This capability is designed to improve overall throughput of the system.

AUTOMATION

Automatic printhead management mechanism and algorithms, allowing for uninterrupted printing with minimal print job set up and preventive maintenance.



TIME

Reduces development cycles times. Enables on-site prototyping in a matter of hours instead of weeks, even for complex designs.

\sim	
(¢)	
$ \mathbf{\Psi} $	

COST

Eliminates need for large order minimums. Enables ability to discover design errors in early development stage with agile rapid prototyping.



COMPLEX GEOMETRIES

Enables increased design capabilities & manufacturability of components. Added agility enables designing, testing and iterating in real time, on site.



COMPONENT CONSOLIDATION

Multi-material Additive Manufacturing enables functional, compact, denser, non-planar electronics parts.

\cap	
I.	

CONFIDENTIALITY

Enables retention of sensitive IP in-house during development. Eliminates concerns and costs related to IP infringement.

<u> </u>

ENVIRONMENTAL

Limits environmental impact through optimized design, size, weight. Reduces waste with additive manufacturing capabilities.





Applications:

- Multi-layer Rigid Printed Circuit Board
- Side contacts
- Vertically integrated ICs
- Printed Capacitors
- RF: Antennas up to 6Ghz,
- Transmission line up to 20Ghz
- Battery Socket
- BGA/SMT mounting
- Inductor: Coils
- Sensors: torque, touch, strain gauge
- Transformers: AC2AC, AC2DC, DC2DC

Industries:

- Aerospace and aviation
- Automotive and industrial
- Defense
- Consumer Electronics and IoT
- Academic and research
- Telecommunications
- Medical devices

Outstanding Performance and Best Maintenance Cost Reduction The DragonFly LDM[™] is the newest edition to the DragonFly

Ine DragonFly LDM™ is the newest edition to the DragonFly family from Nano Dimension, incorporating proprietary, state-of-the-art technlogy that enables 24/7 uninterrupted 3D printing, improved uptime, streamlined workflows and easy operation.

Companies can now reduce demand on prototyping and shortrun manufacturing resources and lower total cost of operation in comparison to traditional manufacturing methods.

The DragonFly LDM offers these benefits:

- High uptime/productivity, including weekends and holidays
- New, automatic print head maintenance and cleaning system
- Simpler and faster operation, including new warm-up plane
- Lower maintenance and operator interactions

Electrifying Additive Manufacturing

Nano Dimension (Nasdaq: NNDM) is a leading additive electronics provider of 3D printed electronics that is disrupting, reshaping, and defining the future of how functional and connected products are made. With its unique additive manufacturing technologies, Nano Dimension targets the growing demand for electronic devices that require sophisticated features. Demand for circuitry, including PCBs, sensors and antennas - which are the heart of electronic devices - cover a diverse range of industries, including consumer electronics, medical devices, defense, aerospace, automotive, IoT and telecom. These sectors can all benefit greatly from Nano Dimension's products and services for short-run manufacturing and rapid prototyping. For more information,

please visit www.nano-di.com







DragonFly LDM[™] Specifications*

Deposition Technology	Piezo drop on demand inkjet	
Number of Printheads	2, one for each lnk	
Minimum Trace Layer Thickness	17 micron	
Minimum Dielectric Layer Thickness	35 micron	
Inks	Nano Dimension Optimized Silver nano particles and dielectric inks	
Trace Conductivity Relative to Copper	5% to 30% process dependent	
Dielectric Constant**	From 2.9 @ 200MHz to 2.69 at 2GHz	
Build Volume	160mm x 160mm x 3mm	
Mechanical Accuracy	0.001mm (1 micron)	
Software	Proprietarty DragonFly and SWITCH	
Extrernal File Compatibility	Gerber, ODB++	
Operating System	Windows	
Network Connectivity	Ethernet TCP/IP 10/100/1000	
Availability	> 85%	
Dimensions	1400mm x 800mm x 1800mm	
Weight	520Kg, (1150 lbs)	
Power Supply***	230VAC, 20A, 50-60Hz	
Operational Temperature	64°F (18°C) to 72°F (22°C)	
Operational Humidity	35% - 55% non-condensing	
Regulatory Compliance	UL, CE, FCC	

* Subject to change ** See Dielectric Properties table *** Must use customer provided UPS

Dielectric Properties Table

Freq	A (50 mm)	
(MHz)	e'	tan (δ)
200	2.90	0.079
500	2.83	0.049
1000	2.81	0.037
2000	2.79	0.026
5000	2.75	0.019
10000	2.74	0.023
15000	2.73	0.016
20000	2.69	0.008

